


Picture	Description	Order no.																								
	Magnetic-operated motor protection switch type MBM (Danfoss) Magnetic-operated motor protection switch 0.85 - 12.0 amp. Designed and tested according to IEC 60947-4-1/EN 60947-4-1.																									
	Coil voltage: 230V AC																									
	Operation temperature: 0°C - 40°C																									
	Protection rating: IP55																									
	Size: 0.85 - 1.50 A	09 200 000																								
	1.20 - 1.90 A	09 201 000																								
	1.80 - 2.80 A	09 202 000																								
	2.70 - 4.20 A	09 203 000																								
4.00 - 6.20 A	09 204 000																									
6.00 - 9.20 A	09 205 000																									
8.00 - 12.00 A	09 206 000																									
	Magnetic-operated motor protection switch type MBM (Danfoss) Magnetic-operated motor protection switch 0.85 - 12.0 amp. Designed and tested according to IEC 60947-4-1/EN 60947-4-1.																									
	Coil voltage: 24V AC																									
	Operation temperature: 0°C - 40°C																									
	Protection rating: IP55																									
	Size: 0.85 - 1.50 A	09 200 100																								
	1.20 - 1.90 A	09 201 100																								
	1.80 - 2.80 A	09 202 100																								
	2.70 - 4.20 A	09 203 100																								
4.00 - 6.20 A	09 204 100																									
6.00 - 9.20 A	09 205 100																									
8.00 - 12.00 A	09 206 100																									
	Hand-operated motor protection switches type HBM with enclosure type ABB IB132-G and motor protection block type ABB MS116 complete																									
	Hand-operated motor protection switch 0.63 - 16.0 amp.																									
	Motor protection switch is temperature compensated. Protects against short-circuit, overload and phase break.																									
	Designed according to standard: IEC/EN 60947-1 IEC/EN 60947-2 IEC/EN 60947-4-1																									
	<table border="1"> <thead> <tr> <th data-bbox="507 1458 863 1525">Size</th> <th data-bbox="863 1458 1353 1525">Short-circuit breaking capacity I_{cs} at 400V AC [kA]</th> <th data-bbox="1353 1458 1501 1525"></th> </tr> </thead> <tbody> <tr> <td data-bbox="507 1525 863 1563">0.63 - 1.00 A</td> <td data-bbox="863 1525 1353 1563">50</td> <td data-bbox="1353 1525 1501 1563">09 211 000</td> </tr> <tr> <td data-bbox="507 1563 863 1601">1.00 - 1.60 A</td> <td data-bbox="863 1563 1353 1601">50</td> <td data-bbox="1353 1563 1501 1601">09 211 100</td> </tr> <tr> <td data-bbox="507 1601 863 1639">1.60 - 2.50 A</td> <td data-bbox="863 1601 1353 1639">50</td> <td data-bbox="1353 1601 1501 1639">09 211 200</td> </tr> <tr> <td data-bbox="507 1639 863 1677">2.50 - 4.00 A</td> <td data-bbox="863 1639 1353 1677">50</td> <td data-bbox="1353 1639 1501 1677">09 211 300</td> </tr> <tr> <td data-bbox="507 1677 863 1715">4.00 - 6.30 A</td> <td data-bbox="863 1677 1353 1715">50</td> <td data-bbox="1353 1677 1501 1715">09 211 400</td> </tr> <tr> <td data-bbox="507 1715 863 1753">6.30 - 10.00 A</td> <td data-bbox="863 1715 1353 1753">50</td> <td data-bbox="1353 1715 1501 1753">09 211 500</td> </tr> <tr> <td data-bbox="507 1753 863 1785">10.00 - 16.00 A</td> <td data-bbox="863 1753 1353 1785">16</td> <td data-bbox="1353 1753 1501 1785">09 211 600</td> </tr> </tbody> </table>	Size	Short-circuit breaking capacity I_{cs} at 400V AC [kA]		0.63 - 1.00 A	50	09 211 000	1.00 - 1.60 A	50	09 211 100	1.60 - 2.50 A	50	09 211 200	2.50 - 4.00 A	50	09 211 300	4.00 - 6.30 A	50	09 211 400	6.30 - 10.00 A	50	09 211 500	10.00 - 16.00 A	16	09 211 600	
	Size	Short-circuit breaking capacity I_{cs} at 400V AC [kA]																								
	0.63 - 1.00 A	50	09 211 000																							
	1.00 - 1.60 A	50	09 211 100																							
	1.60 - 2.50 A	50	09 211 200																							
	2.50 - 4.00 A	50	09 211 300																							
4.00 - 6.30 A	50	09 211 400																								
6.30 - 10.00 A	50	09 211 500																								
10.00 - 16.00 A	16	09 211 600																								
<table border="1"> <tbody> <tr> <td data-bbox="507 1525 863 1563">0.63 - 1.00 A</td> <td data-bbox="863 1525 1353 1563">50</td> <td data-bbox="1353 1525 1501 1563">09 211 000</td> </tr> </tbody> </table>	0.63 - 1.00 A	50	09 211 000	09 211 000																						
0.63 - 1.00 A	50	09 211 000																								
<table border="1"> <tbody> <tr> <td data-bbox="507 1563 863 1601">1.00 - 1.60 A</td> <td data-bbox="863 1563 1353 1601">50</td> <td data-bbox="1353 1563 1501 1601">09 211 100</td> </tr> </tbody> </table>	1.00 - 1.60 A	50	09 211 100	09 211 100																						
1.00 - 1.60 A	50	09 211 100																								
<table border="1"> <tbody> <tr> <td data-bbox="507 1601 863 1639">1.60 - 2.50 A</td> <td data-bbox="863 1601 1353 1639">50</td> <td data-bbox="1353 1601 1501 1639">09 211 200</td> </tr> </tbody> </table>	1.60 - 2.50 A	50	09 211 200	09 211 200																						
1.60 - 2.50 A	50	09 211 200																								
<table border="1"> <tbody> <tr> <td data-bbox="507 1639 863 1677">2.50 - 4.00 A</td> <td data-bbox="863 1639 1353 1677">50</td> <td data-bbox="1353 1639 1501 1677">09 211 300</td> </tr> </tbody> </table>	2.50 - 4.00 A	50	09 211 300	09 211 300																						
2.50 - 4.00 A	50	09 211 300																								
<table border="1"> <tbody> <tr> <td data-bbox="507 1677 863 1715">4.00 - 6.30 A</td> <td data-bbox="863 1677 1353 1715">50</td> <td data-bbox="1353 1677 1501 1715">09 211 400</td> </tr> </tbody> </table>	4.00 - 6.30 A	50	09 211 400	09 211 400																						
4.00 - 6.30 A	50	09 211 400																								
<table border="1"> <tbody> <tr> <td data-bbox="507 1715 863 1753">6.30 - 10.00 A</td> <td data-bbox="863 1715 1353 1753">50</td> <td data-bbox="1353 1715 1501 1753">09 211 500</td> </tr> </tbody> </table>	6.30 - 10.00 A	50	09 211 500	09 211 500																						
6.30 - 10.00 A	50	09 211 500																								
<table border="1"> <tbody> <tr> <td data-bbox="507 1753 863 1785">10.00 - 16.00 A</td> <td data-bbox="863 1753 1353 1785">16</td> <td data-bbox="1353 1753 1501 1785">09 211 600</td> </tr> </tbody> </table>	10.00 - 16.00 A	16	09 211 600	09 211 600																						
10.00 - 16.00 A	16	09 211 600																								

Billede	Beskrivelse	Varenr.																
	<p>Hand-operated mounting motor protection switches the HBM with door mounting kit type ABB DMS132-G and motor protection block type ABB MS116 complete</p> <p>Hand-operated motor protection switch 0.63 - 16.0 amp.</p> <p>Motor protection switch is temperature compensated. Protects against short-circuit, overload and phase break.</p> <p>Designed according to standard: IEC/EN 60947-1 IEC/EN 60947-2 IEC/EN 60947-4-1</p>																	
	<table border="1"> <thead> <tr> <th>Size</th> <th>Short-circuit breaking capacity I_{cs} at 400V AC [kA]</th> </tr> </thead> <tbody> <tr> <td>0.63 - 1.00 A</td> <td>50</td> </tr> <tr> <td>1,00 - 1.60 A</td> <td>50</td> </tr> <tr> <td>1.60 - 2.50 A</td> <td>50</td> </tr> <tr> <td>2.50 - 4.00 A</td> <td>50</td> </tr> <tr> <td>4.00 - 6.30 A</td> <td>50</td> </tr> <tr> <td>6.30 - 10.00 A</td> <td>50</td> </tr> <tr> <td>10.00 - 16.00 A</td> <td>16</td> </tr> </tbody> </table>	Size	Short-circuit breaking capacity I_{cs} at 400V AC [kA]	0.63 - 1.00 A	50	1,00 - 1.60 A	50	1.60 - 2.50 A	50	2.50 - 4.00 A	50	4.00 - 6.30 A	50	6.30 - 10.00 A	50	10.00 - 16.00 A	16	
	Size	Short-circuit breaking capacity I_{cs} at 400V AC [kA]																
	0.63 - 1.00 A	50																
	1,00 - 1.60 A	50																
	1.60 - 2.50 A	50																
	2.50 - 4.00 A	50																
	4.00 - 6.30 A	50																
	6.30 - 10.00 A	50																
10.00 - 16.00 A	16																	
	09 212 000																	
	09 212 100																	
	09 212 200																	
	09 212 300																	
	09 212 400																	
	09 212 500																	
	09 212 600																	

Motor protection switches can be used for all Gram fans type VT, VL, VH and VE 2200 - 4000. All other fan models use frequency converter or Y-D-motor starter.